



## **GMCO HIGH PRESSURE 100R13 FITTING WITH 1502 HAMMER UNION**

2619 Lidstone  
Houston, TX 77023  
800-600-3074  
713-928-2606  
Fax: 713-928-5873



**Use these GMCO fittings** to turn your 2" 100R13 hose into 5,000 PSI Kelly Hose for oil drilling applications. Constructed of A519 seamless material and ferrules are zinc plated chromate finished to provide years of trouble free service. We can ship from stock for fast deliver and allow you to increase sales without increasing your inventory costs. Couplings can be crimped or swaged for ease of installation.

Other end connections available are Male API Thread, Weld Bevel Prep, Pipe Groove, Class 300, 600, 900, 1500, 2500 fixed and floating flanges along with Ring Joint and API Flanges.

**Hose Applications:** 100R13 Hose and 3,000 PSI Slim Hole Hose.

Size	Part Number	Fitting Type	Working Pressure PSI	Ferrule OD X ID	Overall Length	Hose Cut-Off Factor*	Weight Lbs.
2"	1032+1502-F	2" Female 1502 Hammer Union	5000	3 1/2" x 2 7/8"	10 7/8"	7"	22
2"	1032+1502-M	2" Male 1502 Hammer Union	5000	3 1/2" x 2 7/8"	9 1/4"	7"	10.5

***\*Hose Cut-Off Factor***

© George Myer Company