



GMCO GRADE E ROTARY DRILLING SWAGE FITTINGS

2619 Lidstone
Houston, TX 77023
800-600-3074
713-928-2606
Fax: 713-928-5873



GMCO Grade E Rotary Drilling Fittings have set the industry standard were the first swaged-on grade E fitting to be successfully marked in the world. They are a one piece welded design and provide a permanent end connection to high pressure API grade E drilling and vibrator hoses for use in the toughest oil field applications. Constructed of coupling grade schedule XXH N/L 80 4130 and special George Myer spec A 513 DOM tubing materials to provide years of trouble free service. GMCO Grade E Swage Fittings are specially designed for use with a wide variety of manufactures' steel wire reinforced drilling hoses and require no set screws for coupling retention.

End Styles: Include Weld Bevel Prep for the addition of oil field hammer unions along with Ring Joint and API Flanges.

Hose Applications: API Grade E Rotary Drilling & Vibrator Hoses, Cementing Hoses and De-coking Hoses.

SIZE	WORKING PRESS./PSI	PART NUMBER		TYPE	STEM I.D.	STEM MEAN O.D.	WT. LBS.
		WELD BEVEL	WELD BEVEL SHORT				
2 1/2"	7500	940HXXX+48WB-A	940HXXX+48WBS-A	2 1/2" Hose x 3" Connection	2	2 1/2	49
3"	7500	948HXXX+48WB-A	948HXXX+48WBS-A	3" Hose x 3" Connection	2 1/2	3	65
	7500	948HXXX+64WB-A	948HXXX+64WBS-A	3" Hose x 4" Connection	2 1/2	3	62
3 1/2"	7500	956HXXX+64WB-A	956HXXX+64WBS-A	3 1/2" Hose x 4" Connection	3	3 1/2	74
	7500	956HXXX+80WB-A	956HXXX+80WBS-A	3 1/2" Hose x 5" Connection	3	3 1/2	71
4"	7500	964HXXX+80WB-A	964HXXX+80WBS-A	4" Hose x 5" Connection	3 1/2	4	79

© George Myer Company