



## GMCO HEAVY DUTY INDUSTRIAL 316 STAINLESS STEEL FERRULES

2619 Lidstone  
Houston, TX 77023  
800-600-3074  
713-928-2606  
Fax: 713-928-5873



**GMCO Heavy Duty Stainless Steel Ferrules** are constructed to the same standards as GMCO Heavy Duty Carbon Steel Industrial Ferrules but are designed to provide the ultimate in external environmental corrosion and chemical resistance. These fittings are used in conjunction with GMCO Heavy Duty Industrial Stainless Stems and provide permanent attached hose couplings for the harshest environments. Ferrules are kept in stock in stainless steel 316 in sizes from 2" through 6". Pricing on request for larger hoses and other grades of stainless steel. couplings can be crimped or swaged for ease of installation.

**Hose Applications:** Acid, Chemical, Salt Water, Water Jetting, Tank Truck, Material Handling, Multi Purpose Hose.

| HOSE I.D. | HOSE O.D. SIZE RANGE | WORKING PRESSURE PSI | PART NUMBER | FERRULE SIZE |         |        | ACTUAL FERRULE WALL THICKNESS | WEIGHT LBS |
|-----------|----------------------|----------------------|-------------|--------------|---------|--------|-------------------------------|------------|
|           |                      |                      |             | O.D.         | I.D.    | LENGTH |                               |            |
| 2"        | 2 1/2" to 2 5/8"     | 800                  | 4016+32A    | 3            | 2 3/4   | 3 1/2  | .125                          | 1.0        |
|           | 2 5/8" to 2 13/16"   | 800                  | 4016+32F    | 3 1/8        | 2 7/8   | 3 1/2  | .125                          | 1.0        |
| 2 1/2"    | 3" to 3 1/8"         | 800                  | 4016+40A    | 3 1/2        | 3 1/4   | 4 1/4  | .125                          | 1.5        |
|           | 3" to 3 3/8"         | 800                  | 4016+40C    | 4            | 3 9/16  | 4 1/4  | .226                          | 2.8        |
|           | 3 1/8" to 3 5/8"     | 800                  | 4016+40B    | 4            | 3 3/4   | 4 1/4  | .125                          | 1.5        |
| 3"        | 3 1/2" to 3 5/8"     | 800                  | 4016+48A    | 4            | 3 3/4   | 5      | .125                          | 1.8        |
|           | 3 5/8" to 3 7/8"     | 800                  | 4016+48B    | 4 1/2        | 4       | 5      | .237                          | 3.8        |
|           | 3 7/8" to 4"         | 800                  | 4016+48C    | 4 1/2        | 4 1/8   | 5      | .187                          | 3.0        |
|           | 4" to 4 1/8"         | 800                  | 4016+48D    | 4 1/2        | 4 1/4   | 5      | .125                          | 2.0        |
| 4"        | 4 1/2" to 4 3/4"     | 500                  | 4016+64A    | 5 1/4        | 4 7/8   | 5 1/2  | .187                          | 3.0        |
|           | 4 3/4" to 4 15/16"   | 500                  | 4016+64B    | 5 9/16       | 5 1/16  | 5 1/2  | .258                          | 6.0        |
|           | 4 15/16" to 5 1/16"  | 500                  | 4016+64C    | 5 9/16       | 5 3/16  | 5 1/2  | .187                          | 5.0        |
|           | 5 1/8" to 5 3/8"     | 500                  | 4016+64E    | 6            | 5 1/2   | 5 1/2  | .250                          | 5.8        |
| 5"        | 5 3/4" to 6"         | 500                  | 4016+80A    | 6 5/8        | 6 1/8   | 6 7/8  | .250                          | 8.7        |
| 6"        | 6 3/4" to 7"         | 500                  | 4016+96E    | 7 1/2        | 7 1/8   | 7 1/2  | .187                          | 8.0        |
|           | 7 1/8" to 7 3/8"     | 500                  | 4016+96B    | 8            | 7 1/2   | 7 1/2  | .250                          | 12.3       |
|           | 7 3/8" to 7 9/16"    | 500                  | 4016+96C    | 8 3/16       | 7 11/16 | 7 1/2  | .250                          | 12.3       |

*See SWAGE-IT HEAVY DUTY INDUSTRIAL HOSE STEMS for compatible stems.*