



GMCO HEAVY DUTY INDUSTRIAL CARBON STEEL STEMS

2619 Lidstone
Houston, TX 77023
800-600-3074
713-928-2606
Fax: 713-928-5873



GMCO Heavy Duty Industrial Stems, used in conjunction with corresponding ferrules, provide a permanent end connection to rubber industrial hoses for use in the toughest applications. Constructed of pipe grade schedule 40 API 5L Grade B Carbon Steel and zinc plated chromate finish to provide years of trouble free service. GMCO Heavy Duty Swage Stems are longer and heavier than most swage stems on the market and cover a larger range of hose working pressures. Couplings can be crimped or swaged for ease of installation. George Myer also has the largest in stock size range of swage fittings in the industry, covering sizes for 2" through 12" with all conceivable end configurations.

End Styles: Male NPT, Weld Bevel Prep, Pipe Groove, Class 150, 300, 600 fixed and floating flanges.

Hose Applications: Tank Truck, Chemical, Mud Suction, OS&D, Oil Discharge, Frac-Tank, Water Discharge, Water Suction, Water Jetting, Hot Tar & Asphalt, Material Handling, Textile Air Hose, Wire Air Hose, Petroleum, Marine, Dredge and Multi Purpose Hose.

HOSE I.D.	WORKING PRESSURE PSI	PART NUMBER			STEM I.D.	STEM MEAN O.D.	STEM LENGTH	WEIGHT LBS	HOSE CUT-OFF FACTOR*
		MALE PIPE	WELD BEVEL	GROOVE STEM					
2"	800	4100+32	4200+32	4300+32	1 3/4	2	6 1/4	1.5	3"
2 1/2"	800	4100+40	4200+40	4300+40	2 3/16	2 1/2	7 1/2	3	3 3/8"
3"	800	4100+48	4200+48	4300+48	2 9/16	3	8 3/4	3.6	4"
4"	500	4100+64	4200+64	4300+64	3 5/8	4	9 1/2	6.5	4 1/2"
5"	500	4100+80	4200+80	4300+80	4 5/8	5	11 1/2	11.5	5 1/2"
6"	500	4100+96	4200+96	4300+96	5 1/2	6	12 1/4	17	5 5/8"
8"	400	4100+128	4200+128	4300+128	7 1/2	8	13 1/8	26	6"
10"	300	4100+160	4200+160	4300+160	9 3/8	10	16 1/4	46	7 1/2"
12"	300	4100+192	4200+192	4300+192	11 3/8	12	18 1/4	64	7 1/4"

See GMCO HEAVY DUTY INDUSTRIAL HOSE FERRULES for compatible ferrules

GMCO Brand Heavy Duty Stems are stocked in the sizes listed above in Zinc Plated Chromate Finish Carbon Steel.

Contact customer service for availability of other materials and sizes.

* **Hose Cut-Off Factor**

© George Myer Company