



## GMCO SLIM HOLE ROTARY DRILLING SWAGE FITTINGS

2619 Lidstone  
Houston, TX 77023  
800-600-3074  
713-928-2606  
Fax: 713-928-5873



**GMCO Slim Hole Drilling Fittings** are a one piece welded design and provide a permanent end connection to high pressure rubber drilling hoses for use in the toughest oil field applications. Constructed of pipe grade schedule 80 API 5L Grade B Carbon Steel and DOM Tubing and are zinc plated chromate finished to provide years of trouble free service. GMCO Slim Hole Swage Fittings are specially designed for use with steel wire reinforced drilling hoses and require no set screws for coupling retention. These fittings have become the industry standard over the last 25 years.

George Myer also has stock, covering sizes for 2 1/2" x 3" through 3" x 4" with all conceivable end configurations. End styles include but are not limited to Male NPT, Weld Bevel Prep, Pipe Groove, Class 300, 600, 900, 1500, 2500 fixed and floating flanges along with Ring Joint and API Flanges. Other Materials are available such as stainless steel 316.

**Hose Applications:** Slim Hole Drilling Hose, Kelly Hose, Vibrator Hose, Injection and Fracturing.

SIZE	HOSE O.D.	WORKING PRESS./PSI	PART NUMBER		STEM ID	STEM MEAN OD	FERRULE OD X ID	WT. LBS.
			MALE PIPE	WELD BEVEL				
2 1/2"	3 5/8	3000	940HX+48B	940HX+48WB-B	2	2 1/2	4 1/4 X 3 3/4	13.4
	3 5/8	3000	940HX+48C	940HX+48WB-C	2	2 1/2	4 1/2 X 4	14.3
3"	4 1/4	3000	948HX+64B	948HX+64WB-B	2 1/2	3	5 X 4 1/2	19.8

© George Myer Company